INJECTION SYSTEM MANUFACTURER SINCE 1967

- > Low-pressure injection packers
- > High-pressure injection packers
- > Pumps





1148



-00













STAY AHEAD OF THE COMPETITION A proven professional range adapted to the requirements of construction sites.



EFFICIENCY, save time on your job sites with products designed in France since 1967 according to the highest quality standards.


PERFORMANCE, get advice from specialists with tutorials on the methodology and field training.



SERENITY, partner with a company present in more than 37 countries while having a dedicated contact.

SUSTAINABILITY, together let's commit to a better tomorrow.

ROMAIN COTTET Expert, trainer equipment &technique for injection treatments **9** years of experience +33(0)6 26 90 15 28 rcottet@mabi.fr



ENJOY A PREMIUM SERVICE

Reactivity Shipping within 24 hours

Availability Permanent stock, online ordering 24/7

Expertise

Field training in the use of our products

50 YEARS OF INNOVATION Save time, work with confidence & maximum efficiency.



PATENT OF THE 1ST POLYMER INJECTION-PACKER

thanks to a fast in the structure.

EVERY YEAR **MORE THAN 16 MILLION** INJECTION-PACKERS ARE MANUFACTURED IN OUR FACTORIES

SOLUTIONS ADAPTED TO ALL YOUR JOB SITES

FIELDS OF APPLICATION OF MABI INJECTORS

LOW-PRESSURE INJECTION-PACKERS (pressure from 1 to 60 BAR)

Injection of silicate and mineral products.

1
Į
ļ
1

Example: Treatment of rising damp in homogeneous masonry.				
Ø12x47mm	Without head Steel ball 3mm		01080015	
Ø12x65mm	Moulded round head nipple	Steel ball 3mm	01090002	
Ø12x65mm	Flat head	Steel ball 3mm	01090030	
Ø14x65mm	Moulded round head nipple	Steel ball 3mm	01090007	
Ø14x65mm	Flat head	Steel ball 3mm	01090036	

Injection of silicate and mineral products (Cement grout, Filler mortar, Mineral mortar).

Example: Treatment of rising damp in damaged masonry with cavities.

40000	Ø6.5x27mm	Moulded round head nipple	Steel ball 3mm	01010002	
(Lipcon)	Ø6.5x29mm	Flat head	Steel ball 3mm	01010001	
	Ø12x60mm		Without valve (possibility to add a 6.5mm injection-packer)	01090010	
((())))))))))))))))))))))))))))))))))))	Ø12x76mm	Air plug	Without valve (possibility to add a 6.5mm injection-packer)	01090017	

Injection of Acrylic gel Example: Curtain injection


Ø18x77mm	Moulded round head nipple	Steel ball 3mm	01040013
Ø18x80mm	Air plug	Plastic ball 6mm	01040018
Ø18x80mm	Air plug	Without valve	01010086
Caps	Air plug without valve	Allow to stop the blackflow in case of low counter-pressure	01060020


HIGH-PRESSURE INJECTION-PACKERS (maximum pressure 250 BAR)


Injection of reactive resins (PU & PUR, Epoxy).

Example: Concrete crack repair

			From 1 to 150 BAR	
222	Ø12x60mm	Moulded round head nipple	Steel ball 3mm	01090050
			From 20 to 250 BAR	
	Ø10x100 mm	Moulded round head nipple	Spring-loaded valve in the grease nipple	01090100
	Ø14x110 mm	Moulded round head nipple	Spring-loaded valve in the grease nipple	01090101









POLYMER INJECTION-PACKER

PROTECT THE **ENVIRONMENT:**

favour short distribution channels, local production and recyclable materials.



SAVE TIME: MABI injectors, from high quality polymer, have the top part CHOICE OF CONNECTIONS molded onto the injector for quick installation on job sites.

IMPROVE YOUR

EFFICIENCY: with its internal non-return checkvalve patented in 1969, the opening pressure is only 1 BAR. Perfectly watertight use up to 60 BAR.



WITH HEAD



AIR PLUG



WITHOUT HEAD

METAL HIGH-PRESSURE INJECTION-PACKERS

CONVENIENCE Opening pressure of only 20 BAR. Perfectly watertight up to 250 BAR.

PRODUCTIVITY Save time thanks to the defined breaking point line to easily break the packer neck after injection.

USER SAFE	TY
ling in the	С
with the expa	and

ACCESSORIES

A matchless seaconcrete substrate nded rubber sleeve.

ACCESSORIES

DIFFUSING TUBES AND CAPS

Homogeneous spreading into the whole depth due to the 360° micro-holes. Perfect for Damp Proof Course injections.



Tube L=2 M for Ø12/14mm injectors (by unit)	01080024
Cap for Ø12mm tube (by 100 units)	01080020
Tube L=2 M for Ø18mm injectors (by unit)	01040020
Cap for Ø18mm tube (by 100 units)	01040007

EXTENSION RODS



Homogeneous spreading into the whole depth due to the micro-holes. Perfect for curtain injection behind large walls.

=2 M for Ø12/14mm injectors (by unit)	01080025
=2 M for Ø18mm injectors (by unit)	01040021
•	


MOUNTING TOOLS




For setting up the injectors without damaging the connection.

)	For injectors with moulded round head nipple	02010001
	For injectors without head	02010004
	For injectors without head air plug	02010003

6 WWW.SHOP.MABI.FR







7 WWW.SHOP.MABI.FR



HIGH QUALITY MATERIALS FOR PRECISE AND SAFE **INJECTIONS.**

Recommended for the injection of one-component and two-component resins for waterproofing concrete structures and repairing cracks in concrete (epoxy resins, PU, PUR & SPUR polyurethane, methacrylate, etc.).



INJECTION TREATMENT PUMPS

FIELDS OF APPLICATION OF MABI PUMPS

PRODUCTS

	Repair of cracks in concrete structures
חווכפו	Repair of expansion joints
	Quick stopping of water ingress
схаптрие от аррисацо	Filling of cavities in masonry / concrete structures
EXal	Rising damp treatment (DPC)
	Epoxy resin (EP) 1C / 2C
	Polyurethane resin (PU) 1C / 2C
	Expansive polyurethane resin (SPUR)
ncr	Gel acrylates / methacrylates
ype oi pi ouuc	Aqueous solution based on Silicate / Siloxane / Silane / Siliconate
iype	Silicate / Siloxane / Silane / Siliconate gel or cream

ADVANTAGES

Technology	Manual lever	Diaphragm	Piston	Diaphragms
MAXIMUM PRESSURE (BAR)	100	220	227	25
MAXIMUM FLOW (L / MIN)	approx. 1.9 ccm / stroke lever	4.5	2.0	25
MOTOR	-	Electric 230V 50Hz 1.5Kw	Electric 230V 50Hz 0.74Kw	Electric 230V 50Hz 1.5Kw
DIMENSIONS	356 x 125 x 67,5 mm	47x 32x44cm	41x35x47 cm	52x32x31.5 cm
WEIGHT (KG)	0.96	27	14	28
REFERENCE	03060201	03090645	03300100	03090300

9 WWW.SHOP.MABI.FR

RELIABILITY: MADE FROM HIGH QUALITY COMPONENTS

MAB

MANUAL PUMP 550CCM	AIRLESS MABI 4.5L	AIRLESS GRACO 395 PC PRO	MABI PUMP 25BP	
V	V	V	-	
-	-	-	-	
-	V	V	-	
-	V	V	-	
-	V	-	٧	
V	V	V	-	
V	V	V	-	
V	V	V	-	
-	-	-	-	
-	V	-	V	
-	V	-	-	
ECONOMICAL & LIGHT	ROBUST & VERSATILE	PROVEN & RESISTANT	PRODUCTIVE & Modular	
Ideal for hard-to- reach places with a small amount of product.	A true ally for any type of job site. Simplified mainte- nance.	High-torque brushless motor for better longevity.	High flow, adjus- table according to your needs.	



MAB



MABI 25 BP

COMFORT

Adjustable frame with tailor-made options to better meet your needs. Telescopic handle and 20CM wheels to easily move the pump on your job sites. Easy hose storage with the integrated hose reel.

QUALITY

High-performance engine for endurance and long lifespan. Polymer body pump for better resistance to Damp Proof Course chemicals.

QUALITY

MOBILITY

Ease of maintenance, separation of engine & body pump, without electronics. Tungsten carbide plugs and stainless-steel valves to increase your pump's lifespan.

Lightweight and space-saving

for easy movement on all your job sites. Stability of the

pump in operation with the anti-vibration silentblock.

SAFETY

Pressure stability for precise injections. Easy product handling with optional 6L hopper.

> **PROFITABILITY** Versatility of use. Heavy duty use with cooling fins.

Videos :

Setup & startup the Airless 4.5L pump

Advice on use and maintenance

CLICK HERE

SAFETY

Protection and storage of the power cord.

PROFITABILITY

High flow rate to improve your productivity on construction sites. Easy maintenance.

Videos:

- Setup & startup the 25BP pump

- Advice on use and maintenance

CLICK HERE



EUROPEAN LEADER, MABI MEETS THE NEEDS OF PROFESSIONALS IN MORE THAN 37 COUNTRIES AROUND THE WORLD

SINCE 1967 DOZENS OF INNOVATIONS THAT HAVE REVOLUTIONIZED THE WAY YOU WORK.

All information is provided for information purposes only and is subject to change.



MABI SARL ZAC DES SAULES - 90400 BOTANS - FRANCE TÉL. : +33 (0)3 84 56 17 44 INFO@MABI.FR - WWW.SHOP.MABI.FR